

# Device Connector

Vendor Neutral, Long Range Wireless Bridge.



More than a repeater, the Device Connector is a complete wireless network extension solution with advanced TruePower technology that keeps signals clean, clear, and strong from start to finish. And it's compatible with any access point and available in three rugged enclosure styles, so you can just drop it in and go – no network reconfiguration or device upgrades needed.

## The Coverage You Need. Made Plug-and-Play Easy.

Easily extend Wi-Fi coverage in minutes with Pepwave's Device Connector. The Device Connector gets your devices talking over a large area without wires or configuration headaches. And because it works transparently at Layer 2, the Device Connector is compatible with any access point, so there's no need to upgrade your gear to get industry-leading Wi-Fi range and performance.

## Reliability in Extreme Environments.

The Device Connector is designed and manufactured with the strictest standards. It is rated to operate in almost any environment imaginable. It is just as comfortable working in desert, marine, and arctic environments as it is in the office, making it the ultimate go-anywhere drop-in solution.

## CarFi Fast Roaming. WAN Reliability with Wi-Fi Mobility (Add-on Feature. Available Soon.).

CarFi Fast Roaming, available as an optional software upgrade, lets your Device Connector hop from AP to AP in a matter of seconds. Seamlessly. Without dropouts or downtime. Whether you're commanding an emergency situation, coordinating a construction project, or keeping the shelves stocked in a supermarket or warehouse, CarFi Fast Roaming keeps everyone communicating at all times.

## TruePower Device Bridging. Strong Signals End-to-End.

The Peplink Device Connector features our TruePower RF technology, which delivers maximum transmission power across all links at even the highest data rates. With TruePower, you get reliable, fast connections at distances that put other radios out of reach.


## Three Durable Enclosures. A Device Connector for Every Job.

Whether you work indoors or outdoors, in a clean, quiet office or on a dirty, noisy construction site, there's a Device Connector model built just for you. For indoor applications, there's our rugged metallic enclosure. For medium-duty outdoor installations, such as a factory floor, there's our IP55 high-impact plastic enclosure. And for those jobs that make other equipment run and hide, there's our aircraft-grade aluminum IP67 housing, tough as nails and ready to handle just about anything you or Nature can throw at it.


# Specifications

|                        | Device Connector Rugged  | Device Connector IP55  |
|------------------------|--|--|
| Product Code           | DCS-RUG  | DCS-GN-IP55  |
| Wi-Fi Interface        |  |  |
| Data Rate              | 1750Mbps   | 1166Mbps   |
| 802.11b/g/n Wi-Fi      | ●  | ●  |
| 802.11ac/a/n Wi-Fi     | ●  | ○  |
| Transmit Power         | 2412 - 2472 MHz: 24dBm (FCC)/17dBm (CE)<br>5180 - 5825 MHz: 22dBm (FCC)/17dBm (CE)       | 2412 - 2472 MHz: 6dBm<br>5180 - 5825 MHz: 9dBm                                   |
| Built-in Wi-Fi Antenna | ○  | ●  |
| Ethernet Interface     |  |  |
| Ethernet Ports         | 2(GE)  | 2(GE)  |
| Hardware Features      |  |  |
| Enclosure              | Indoor Metal   | IP55 Outdoor Enclosure   |
| Dimension              | 5.8 x 5.0 x 1.6 inches<br>147 x 128 x 40 mm  | 10.6 x 3.3 x 1.2 inches<br>270 x 85 x 31 mm                                      |
| Weight                 | 0.93 pounds<br>420 grams   | 0.89 pounds<br>405 grams   |
| Power Input            | AC Adapter: AC Input 100V to 240V,<br>DC Output 12V, 2A,<br>Terminal Block: 12V - 36V DC | AC Adapter: AC Input 100V-240V,<br>DC Output 24V, 1A,<br>Passive PoE: 24V DC, 1A |
| Power Consumption      | 13W (max.)   | 25W (max.)   |
| Operating Temperature  | -4° - 149°F<br>-20° - 65°C   | -40 - 122°F<br>-40 - 50°C  |
| Humidity               | 15% - 95% (non-condensing)   |  |
| Certifications         | FCC, CE, RoHS  |  |
| Warranty               | 1-Year Limited Warranty  |  |

## Device Connector Rugged



## Device Connector IP55



# Product Ordering Information

## Device Connector - Indoor Rugged

| Product Code | Product Name            | Description  |
|--------------|-------------------------|--|
| DCS-RUG      | Device Connector Rugged | 802.11ac/a/b/g/n 3x3 MIMO 1750Mbps layer 2 client bridge in metallic indoor enclosure. Manageable by InControl2 cloud management tool. |

## Device Connector - Outdoor IP55 Compact

| Product Code | Product Name          | Description   |
|--------------|-----------------------|---|
| DCS-GN-IP55  | Device Connector IP55 | 802.11ac/a/b/g/n 1166Mbps layer 2 client bridge in waterproof IP55 outdoor enclosure. Manageable by InControl cloud management. |

## Mounting Accessory for IP55 Models

| Product Code | Compatible With | Description   |
|--------------|-----------------|---|
| ACW-510      | DCS-GN-IP55     | Wall/pole mount with flexible ball joint for high-precision installation. |

IP55

www.peplink.com



©Peplink. All rights reserved. Pepwave, the Pepwave logo, and SpeedFusion are trademarks of Peplink Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. All specifications are subject to change without notice.